

QUARTZ STYLE

20MM EXTERNAL LEVATO MONO PAVER

2 colours






- Quartz Style is a range interpreting natural quartzite, offering gently varying shades and distinctive stone markings.
- Textured surface.
- Available in a 10mm thickness for indoor coordination.









Variation

Please Note: Tones in these images are indicative. Real samples can be requested for free.

TECHNICAL INFORMATION

	FORMAT SIZE	FINISH	THICKNESS	SLIP RESISTANCE
1	600 x 600	Textured	20mm	R12 (C)

Please Note: All sizes are nominal. If required, please contact us for exact working sizes.

All porcelain tiles have rectified edges.

BREAKING STRENGTH	ISO 10545 - 4	>13.000N	
POINT LOAD	EN 12825	CENTRE SIDE CENTRE DIAGONAL	600x600 6,87kN 4,61kN 6,44kN
RESISTANCE TO ABRASION	ISO 10545 - 6	<150mm³	

Please Note: For voids in excess of 100mm, Surface 360 recommends using our Impact Control Membrane (ICM). To be applied to the underside of paving, in all affected areas.

For a Raised Installation: Required pedestal positions based on size.



Sizes:

SURFACE 360

QUARTZ STYLE

10MM INTERNAL LEVATO PORCELAIN TILE

2 colours






- Quartz Style is a range interpreting natural quartzite, offering gently varying shades and distinctive stone markings.
- Natural and polished surface finishes available.
- Available in a 20mm thickness for outdoor coordination.









Please Note: Tones in these images are indicative. Real samples can be requested for free.

TECHNICAL INFORMATION

	FORMAT	 		•	Sizes:
	SIZE	FINISH	THICKNESS	SLIP RESISTANCE	300 x 300
1	300 x 300	Natural	10mm	R10 (B)	300 X 300
2	300 x 600	Natural	10mm	R10 (B)	300 x 600
2	300 x 600	Polished	10mm	D10 (D)	
3	600 x 600 600 x 600	Natural Polished	10mm 10mm	R10 (B)	600 x 600

Please Note: All sizes are nominal. If required, please contact us for exact working sizes.

All porcelain tiles have rectified edges.

2 +44 (0)118 391 4120