


RAW **20MM EXTERNAL LEVATO MONO PAVER**

3 3 SIZES COLOURS FINISH



- Textured surface.
- Available in a 10mm thickness for indoor coordination.










COLOURS





Variation

Please Note: Tones in these images are indicative. Real samples can be requested for free.

TECHNICAL INFORMATION


02

1 600 x 600 Textured 20mm R11 (A, B & C) 2 600 x 1200 Textured 20mm R11 (A, B & C)		FORMAT SIZE	FINISH	THICKNESS	SLIP RESISTANCE
3 800 x 800 Textured 20mm R11 (A, B & C)	2	600 x 1200	Textured	20mm	R11 (A, B & C)


Please Note: All sizes are nominal. If required, please contact us for exact working sizes. All porcelain tiles have rectified edges

BREAKING STRENGTH	ISO 10545 - 4	>13.000N
RESISTANCE TO ABRASION	ISO 10545 - 6	<175mm³

Please Note: For voids in excess of 100mm, Surface 360 recommends using our Impact Control Membrane (ICM). To be applied to the underside of paving, in all affected areas.



For a Raised Installation: Required pedestal positions based on size.



SURFACE 360





4 SIZES





COLOURS 02 03

Please Note: Tones in these images are indicative. Real samples can be requested for free.

TECHNICAL INFORMATION

	FORMAT SIZE	FINISH	THICKNESS	2
1	300 x 600	Natural	10mm	
2	600 x 600	Natural	10mm	
3	600 x 1200	Natural	10mm	
4	800 x 800	Natural	10mm	

Please Note: All sizes are nominal. If required, please contact us for exact working sizes. All porcelain tiles have rectified edges.

• www.surface360.co.uk

Please visit our website or contact Surface 360 regarding the 'Sustainable Accreditations' for this tile range.

info@surface360.co.uk

RAW 10MM INTERNAL LEVATO PORCELAIN TILE

• Raw is a collection consisting of three raw metal shades, giving any space texture and depth.

• Natural finish.

· Available in a 20mm thickness for outdoor coordination.





Sizes:





600 x 600

600 x 1200



Please visit our website or contact Surface 360 regarding the 'Sustainable Accreditations' for this tile range.